

HVAC

VALVES AND VALVE ACCESSORIES

ISOLATION VALVES					
	Code	Size DN (mm)			
HERZ Isolation Valve Female Thread, DZR 	HVS/12100-19	8	RuB Isolation Valve Female Thread, Extended Thread Nickel Plated 	BVT201/008	8
	HVS/12190-01	15		BVT201/010	10
	HVS/12190-02	20		BVT201/015	15
	HVS/12190-03	25		BVT201/020	20
	HVS/12190-04	32		BVT201/025	25
	HVS/12190-05	40		BVT201/032	32
	HVS/12190-06	50		BVT201/040	40
	HVS/12100-07	65		BVT201/050	50
HERZ Isolation Valve Female Thread, DZR Brass, Red Top  EXTENDED HANDLES That will protrude beyond 38mm insulation	HVS/12206-41	15	Isolation Valve Female Thread Stainless Steel Full Bore 2-Piece 	BVT201/065	65
	HVS/12206-42	20		BVT201/080	80
	HVS/12206-43	25		BVT201/100	100
	HVS/12206-44	32		VMBVSS2/008	8
	HVS/12206-45	40		VMBVSS2/010	10
	HVS/12206-46	50		VMBVSS2/015	15
				VMBVSS2/020	20
				VMBVSS2/025	25
HERZ Isolation Valve Female Threads, DZR Brass, Blue Top  EXTENDED HANDLES That will protrude beyond 38mm insulation	HVS/12206-51	15	Isolation Valve Female Thread Stainless Steel Full Bore 2-Piece 	VMBVSS2/032	32
	HVS/12206-52	20		VMBVSS2/040	40
	HVS/12206-53	25		VMBVSS2/050	50
	HVS/12206-54	32		VMBVSS2/065	65
	HVS/12206-55	40		VMBVSS2/080	80
	HVS/12206-56	50		VMBVSS/008	8
				VMBVSS/010	10
				VMBVSS/015	15

REGULATION VALVES					
	Code	Size DN (mm)			
HERZ Regulation Valve Fixed Orifice, DZR Brass, BSP Threads 	HVS/14017-11	15 - LOW FLOW	HERZ Regulation Valve PN16 Flanged 	HVS/14218-47	65
	HVS/14017-21	15 - MEDIUM FLOW		HVS/14218-48	80
	HVS/14017-01	15		HVS/14218-49	100
	HVS/14017-02	20		HVS/14218-50	125
	HVS/14017-03	25		HVS/14218-51	150
	HVS/14017-04	32			
	HVS/14017-05	40			
	HVS/14017-06	50			
HERZ Regulation Valve Variable Orifice DZR Brass, BSP Threads 	HVS/14217-01	15	HERZ Regulation Valve Compact / PN16 Flanged Version 	HVS/14218-81	65
	HVS/14217-02	20		HVS/14218-82	80
	HVS/14217-03	25		HVS/14218-83	100
	HVS/14217-04	32		HVS/14218-84	125
	HVS/14217-05	40		HVS/14218-85	150
	HVS/14217-06	50		HVS/14218-86	200
	HVS/14217-07	65		HVS/14218-87	250
	HVS/14217-08	80		HVS/14218-88	300

HVAC

VALVES AND VALVE ACCESSORIES

PICV - PRESSURE INDEPENDENT CONTROL VALVES

	Code	Size DN (mm)			Code	Size DN (mm)
PICV, DZR Brass Male Threads - BSP 	HVS/14006-11	15	SMART PICV, DZR Brass, Female Threads - BSP 		HVS/14006-21	15
	HVS/14006-12	20			HVS/14006-22	20
	HVS/14006-13	25				
	HVS/14006-14	32				
	HVS/14006-15	40				
	HVS/14006-16	50				
PICV, DZR Brass Female Threads - BSP 	HVS/14206-11	15	SMART PICV, DZR Brass Female Threads - BSP 		HVS/14206-21	15
	HVS/14206-12	20			HVS/14206-22	20
	HVS/14206-13	25				
	HVS/14206-14	32				
	HVS/14206-15	40				
	HVS/14206-16	50				
	PICV, Cast Iron PN16 Flanged PN16 Rated 				HVS/F4006-62	50
					HVS/F4006-63	65
					HVS/F4006-64	80
					HVS/F4006-65	100
					HVS/F4006-66	125
					HVS/F4006-67	150
					HVS/F4006-68	200

PICV ACTUATORS

		Code			Code
PICV Actuators to go with 4006 / 4026 / 4206 SMART- PICV 	24V for 3-point	HVS/17708-40	PICV Actuators to go with Flanged 4006 Valves (57-68)	24V modulating / 500 N  suits F4006 DN15 to 80 Flanged Control Valves (c/w fitting 17712-20)	HVS/F7712-29
	230V for 3-point	HVS/17708-41			
	24V for 0-10V DC Signal (Modulating)	HVS/17708-42			HVS/F7712-31
				24V modulating / 1000 N  suits F4006 DN50-65-80 Flanged Control Valves	


HVAC

VALVES AND VALVE ACCESSORIES

DIFFERENTIAL PRESSURE CONTROLLER

	Code	Size DN (mm)	Pressure (kPa)		Code	Size DN (mm)	Pressure (kPa)
Differential Pressure Controller, DZR Brass Male Threads - BSP 	HVS/14002-41	15	5 - 30	Differential Pressure Controller PN16 Flanged 	HVS/F4007-07	65	10-40
	HVS/14002-42	20	5 - 30		HVS/F4007-17	65	20-80
	HVS/14002-43	25	5 - 30		HVS/F4007-27	65	50-150
	HVS/14002-44	32	5 - 30		HVS/F4007-08	80	10-40
	HVS/14002-45	40	5 - 30		HVS/F4007-18	80	20-80
	HVS/14002-46	50	5 - 30		HVS/F4007-28	80	50-150
	HVS/14002-61	15	25-60		HVS/F4007-09	100	10-40
	HVS/14002-62	20	25-60		HVSF40071-9	100	20-80
	HVS/14002-63	25	25-60		HVS/F4007-29	100	50-150
	HVS/14002-64	32	25-60		HVS/F4007-10	125	10-40
	HVS/14002-65	40	25-60		HVS/F4007-20	1325	20-80
	HVS/14002-66	50	25-60		HVS/F4007-30	125	50-150
					HVS/F4007-11	150	10-40
					HVS/F4007-21	150	20-80
					HVS/F4007-31	150	50-150

2-PORT AND 3 PORT VALVES

	Code	Size DN (mm)		Code	Size DN (mm)
2-Port Valve PN16 Flanged 	HVS/14035-01	15 (Kvs 1)	3-Port Control Valve, PN16 Flanged 	HVS/14037-01	15 (Kvs 1)
	HVS/14035-11	15 Kvs 1.6)		HVS/14037-11	15 Kvs 1.6)
	HVS/14035-21	15 (Kvs 2.5)		HVS/14037-21	15 (Kvs 2.5)
	HVS/14035-31	15 (Kvs 4)		HVS/14037-31	15 (Kvs 4)
	HVS/14035-03	25 (Kvs 6.3)		HVS/14037-03	25 (Kvs 6.3)
	HVS/14035-13	25 (Kvs 10)		HVS/14037-13	25 (Kvs 10)
	HVS/14035-04	43		HVS/14037-04	43
	HVS/14035-05	40		HVS/14037-05	40
	HVS/14035-06	50		HVS/14037-06	50
	HVS/14035-07	63		HVS/14037-07	63
	HVS/14035-08	80		HVS/14037-08	80
	HVS/14035-09	100		HVS/14037-09	100
	HVS/14035-10	125	3-Port Mixing and Diverting Valve, DZR Brass, BSP Threads 	HVS/14037-10	125
	HVS/14035-41	150		HVS/14037-41	150
				HVS/14037-15	15
				HVS/14037-20	20
				HVS/14037-25	25
				HVS/14037-32	32
				HVS/14037-40	40
				HVS/14037-50	50

2 AND 3-PORT VALVE ACTUATORS

	Code		Code
Actuators to go with 4035 and 4037 Flanged Valves	24V modulating 2500 N 	HVS/17712-31	Actuators to go with 4037 DZR Brass 3-Port Valves
	Suits DN65-80		
	24V modulating 2500 N 	HVS/17712-32	
	Suits DN100-150		
Actuators to go with 4037 DZR Brass 3-Port Valves	24V modulating 500 N 	HVS/17712-29	Actuators to go with 4037 DZR Brass 3-Port Valves
	Suits DN15-25		
	24V modulating 1000 N 	HVS/17712-31	
	Suits DN32-50		

HVAC

VALVES AND VALVE ACCESSORIES

SPECIALISED VALVES SETS

	Code	Size DN (mm)			Code	Size DN (mm)
CONNECT 4 Fan Coil Valve  <						

SPECIALISED VALVES SET ACTUATORS

		Code			Code
Actuators for HerzCon and Connect 4 Units 	24V for 3-point	HVS/17708-40	Actuators for Connect4 with 14037 3-Way Valve 	24V / (0-10V)	HVS/17712-11
	230V for 3-point	HVS/17708-41		suits DN15-25	
	24V for 0-10V DC Signal (Proportional)	HVS/17708-42		230V / 2 or 3POS	HVS/17712-50
				suits DN15-25	
				24V / 2 or 3POS /	HVS/17712-51
				suits DN15-25	

NON RETURN VALVES

	Code	Size DN (mm)			Code	Size DN (mm)
EUROPA Bronze Non Return Valve BSP Threads 	BVEC/010	10	Non Return Valve, Dual Disc  Body - Cast Iron Spring - 316 SS Disc - 316 SS, Seat - EPDM Shaft - 304/316 SS Flange Gasket - 316 SS Max Temp -120°C Max Pressure - 16Bar		ACVCI316/050	50
	BVEC/015	15			ACVCI316/065	65
	BVEC/020	20			ACVCI316/080	80
	BVEC/025	25			ACVCI316/100	100
	BVEC/032	32			ACVCI316/125	125
	BVEC/040	40			ACVCI316/150	150
	BVEC/050	50			ACVCI316/200	200
	BVEC/065	65			ACVCI316/250	250
	BVEC/080	80			ACVCI316/300	300
	BVEC/100	100			ACVCI316/350	350
Non Return Valve, Single Disc  Body - Cast Iron Spring - 316 SS Disc - 304 SS, Seat - EPDM Hinge Pin - 304 Flange Gasket - NBR Max Temp -120°C Max Pressure - 16Bar	ACVSW/050	50			ACVCI316/400	400
	ACVSW/065	65				
	ACVSW/080	80				
	ACVSW/100	100				
	ACVSW/125	125				
	ACVSW/150	150				
	ACVSW/200	200				
	ACVSW/250	250				
	ACVSW/300	300				
	ACVSW/350	350				
	ACVSW/400	400				

HVAC

VALVES AND VALVE ACCESSORIES

KITZ FIGURE DJ WAFER AND LUGGED BUTTERFLY VALVES

KITZ BUTTERFLY VALVES, CONCENTRIC WITH BONDED SEAT

DN 50-300, EPDM/NBR liner for drinking water, SS 1.4408 disc

Kitz Figure DJ range of concentric butterfly valves are available in wafer and lug design with lever and gearbox.

The design has bonded seats and spherical design for discs and seats to minimise wear and prolong service life.

The valve is available with EPDM and NBR Linings and has a low operating torque.

	Code	Size NB (mm)	MATERIALS		SPECIFICATIONS
			Part	Material	
Kitz Lugged Butterfly Valve, Table E, EPDM 	VBFLEE050	50	Body	Ductile Iron	Flanges - Lugged AS2129 D/E EN 1092 PN 10/16 ANSI 125/150
	VBFLEE065	65	Handle / Gear-box	Aluminium	
	VBFLEE080	80			
	VBFLEE100	100	Disc	316 Stainless Steel	Cold Working Pressure 1600 Kpa MAX Working Temperature EPDM 110°C
	VBFLEE125	125	Seat	EPDM or NBR	
	VBFLEE150	150	Bushing	Epoxy Glass Fibre Composite	
	VBFLEE200	200			MAX Working Temperature Nitrile 80°C Size 50-300 NB Lever Handle 50-200mm, Gearbox 250-300mm
	VBFLEE250	250	Notch Plate	316 Stainless Steel	
	VBFLEE300	300	O-Ring	EPDM or Nitrile	

	Code	Size NB (mm)	MATERIALS		SPECIFICATIONS
			Part	Material	
Kitz Wafer Butterfly Valve, EPDM 	VBFW050	50	Body	Ductile Iron	Flanges - Wafer Universal: AS2129 D/E EN 1092 PN 10/16 ANSI 125/150
	VBFW065	65	Handle / Gear-box	Aluminium	
	VBFW080	80			
	VBFW100	100	Disc	316 Stainless Steel	Cold Working Pressure 1600 Kpa MAX Working Temperature EPDM 110°C
	VBFW125	125	Seat	EPDM or NBR	
	VBFW150	150	Bushing	Epoxy Glass Fibre Composite	
	VBFW200	200			MAX Working Temperature Nitrile 80°C Size 50-300 NB Lever Handle 50-200mm, Gearbox 250-300mm
	VBFW250	250	Notch Plate	316 Stainless Steel	
	VBFW300	300	O-Ring	EPDM or Nitrile	

ORIFICE PLATES

	Code	Size DN (mm)
HERZ Orifice Plate, Stainless Steel  Max Temp. 130C Max Pres. 20bar	HVS/14000-31	65
	HVS/14000-32	80
	HVS/14000-33	100
	HVS/14000-34	125
	HVS/14000-35	150
	HVS/14000-36	200
	HVS/14000-37	250
	HVS/14000-38	300
	HVS/14000-39	350
	HVS/14000-40	400
	HVS/14000-41	450
	HVS/14000-42	500
	HVS/14000-43	600

STRAINERS

	Code	Size DN (mm)
HERZ Strainer, DZR Brass Female Thread - BSP 	HVS/12662-01	15
	HVS/12662-02	20
	HVS/12662-03	25
	HVS/14111-14	32
	HVS/14111-15	40
	HVS/14111-16	50
MECH Strainer, Flanged Table E 	HWS/050	50
	HWS/065	65
	HWS/080	80
	HWS/100	100
	HWS/125	125
	HWS/150	150
	HWS/200	200
	HWS/250	250
	HWS/300	300
	HWS/350	350
	HWS/400	400

HVAC

VALVES AND VALVE ACCESSORIES

PRESSURE REDUCING VALVES

	Code	Size DN (mm)			Code	Size DN (mm)
ITAP Pressure Reducing Valve, 1-6bar adjustment BSP Threads 	BVPR143/025	25		ITAP Pressure Reducing Valve, 1-4bar adjustment BSP Threads 	BVPR361/015	15
	BVPR143/032	32			BVPR361/020	20
	BVPR143/040	40				
	BVPR143/050	50				
				HERZ Pressure Reducing Valve, 0.5-6bar adjustment BSP Threads 	HVS/12682-11	15

PRESSURE RELIEF VALVES

	Code	Inlet DN (mm)	Outlet DN (mm)			Code	Inlet DN (mm)	Outlet DN (mm)
FLAMCO Prescor Pressure Relief Valve BSP Threads 	FLSV015/27606 (4 BAR)	15	15	FLAMCO Prescor Solar Pressure Relief Valve BSP Threads 		FLSVS015/28310	15	10-40
	FLSV020/27028 (4 BAR)	20	20			FLSVS015/28311	15	
	FLSV025/27045 (3 BAR)	25	32			FLSVS015/28316	20	
	FLSV025/27049 (5 BAR)	25	32			FLSVS015/28321	25	
	FLSV032/27056 (3 BAR)	32	40	HERZ Pressure Relief Valve BSP Threads 		HVS/FLSV025/6BAR	25	
	FLSV032/27039 (5 BAR)	32	40			HVS/FLSV032/6BAR	32	
	FLSV032/29209 (7 BAR)	32	40					

REDUCED PRESSURE ZONE VALVES (RPZ VALVES)

	Code	Size DN (mm)
Reduced Pressure Zone Valves (RPZ Valves) BSP Threads 	RPZ/W19375	20
	RPZ/W25375L	25
	RPZ/W32375L	32
	RPZ/W40375L	40
	RPZ/W50375L	50
	RPZ/W65375L	65
	RPZ/W80375L	80

DRAIN COCKS

	Code	Size DN (mm)
Drain Cock 	HVS/12512-01	15

HVAC

VALVES AND VALVE ACCESSORIES

AIR VENTS					
	Code	Size DN (mm)		Code	Size DN (mm)
Flamco Flexvent 	FLAV/27750	10	Flamco Flexvent Super 	FLAVSUPER/28520	20
	FLAV/27740	15			
	FLAV/27735	20			
Flamco Flexvent Max 	FLAVMAX/28550	20	ITAP 	HVAR/008	8
				HVAR/015	15

RUBBER FLEX JOINTS					
	Code	Size DN (mm)		Code	Size DN (mm)
Rubber Flex Joint Single Bellow Table E 	FLFLEX/050TE	50	Rubber Flex Joint Double Bellow, Table E 	FLFLEX/080TED	80
	FLFLEX/065TE	65		FLFLEX/100TED	100
	FLFLEX/080TE	80		FLFLEX/125TED	125
	FLFLEX/100TE	100		FLFLEX/150TED	150
	FLFLEX/125TE	125		FLFLEX/200TED	200
	FLFLEX/150TE	150	Rubber Flex Joint BSP Threads 	FLFLEX/250TED	250
	FLFLEX/200TE	200		FLFLEX/300TED	300
	FLFLEX/250TE	250		FLFLEX/025BSP	25
	FLFLEX/300TE	300		FLFLEX/032BSP	32
	FLFLEX/350TE	350		FLFLEX/040BSP	40
	FLFLEX/400TE	400		FLFLEX/050BSP	50
	FLFLEX/450TE	450			

BINDER TEST PLUGS					
	Code	Size DN (mm)		Code	Size DN (mm)
Binder Test Plug, DZR, Blue Top 	HVS/0284-01	8	Extended Binder Test Plug, DZR, Blue Top 	HVS/0284-11	8
Binder Test Plug, DZR, Red Top 	HVS/0284-02	8	Extended Binder Test Plug, DZR, Red Top 	HVS/0284-12	8

GAUGES					
	Code	Size DN (mm)		Code	Size DN (mm)
Pressure Gauge 1.5-3bar, 63mm Face, BSP Threads 	FLPG63/27210	8	Pressure Gauge 3bar, 63mm Face, BSP Threads 	FLPG63/27205	8
Pressure Gauge 1.5-3bar, 80mm Face, BSP Threads 	FLPG80/27222	8	FLAMCO Pressure and Temperature Gauge 1.5 - 3bar, 63mm Face  (With shut-off valve)	FLPTG/27250	15

HVAC

VALVES AND VALVE ACCESSORIES

FLEXIBLE HOSES					
	Code	Size DN (mm)			
HERZ Stainless Steel Braided Hose, PN25, 1000mm 	HHS1000/020	20	HERZ Stainless Steel Braided Hose, PN25, 400mm 	HHS400/020	20
	HHS1000/025	25		HHS400/025	25
	HHS1000/032	32		HHS400/032	32
	HHS1000/040	40		HHS400/040	40
				HHS400/050	50
HERZ Stainless Steel Braided Hose, PN25, 600mm 	HHS600/020	20			
	HHS600/025	25			
	HHS600/032	32			
	HHS600/040	40			
	HHS600/050	50			

HVAC

TANKS AND VESSELS


AIR AND DIRT SEPARATORS

	Code	Size NB (mm)			Code	Size DN (mm)
FLAMCO PN16 Flanged / PN16 rated 	FLASCM/28080	50		FLAMCO SMART PN16 Flanged / PN16 rated 	FLACM/31041	50
	FLASCM/28081	65			FLACM/31042	65
	FLASCM/28082	80			FLACM/31043	80
	FLASCM/28083	90			FLACM/31044	90
	FLASCM/28084	100			FLACM/31045	100
	FLASCM/28085	150			FLACM/31046	150
	FLASCM/28086	200			FLACM/31047	200
				FLAMCO ECOPlus BSP threads	FLASCM/30051	¾" (DN20)
					FLASCM/30052	(DN22)
					FLASCM/30053	1" (DN25)
					FLASCM/30054	1¼" (DN32)
					FLASCM/30055	1½" (DN40)
					FLASCM/30056	2" (DN50)
Max Temp - 120°C Max Pre - 10 bar				Max Temp - 120°C Max Pre - 10 bar		

EXPANSION VESSELS

	Code	Size			Code	Size
Wall Mounted Expansion Vessels 	FLEV8/16008	8L		Side Mounted Expansion Vessels 	FLEVP18/13316	18L
	FLEV12/16015	12L			FLEVP25/13326	25L
	FLEV18/16020	18L			FLEVP35/13336	35L
	FLEV25/16027	25L			FLEVP50/13357	50L
Max Temp - 120°C Max Pre - 6 Bar Max Temp Diaphragm - 70°C				Max Pre - 3 Bar Max Temp Diaphragm - 70°C		
Foot Mounted Expansion Vessels 	FLEV35/16037	35L		Mounting Options 	FLWM27913	2 - 2.5 litres Vessels
	FLEV50/16053	50L			FLWM/27910	8 - 25 litres Vessels *Bracket Only
	FLEV80/16084	80L			FLWM27996	8 - 25 litres Vessels
	FLEV110/16119	110L				
	FLEV140/16141	140L				
	FLEV200/16208	200L				
	FLEV300/16304	300L				
	FLEV425/16424	425L				
	FLEV600/16604	600L				
	FLEV800/16804	800L				
Max Temp - 120°C Max Pre - 6 Bar Max Temp Diaphragm - 70°C	FLEV1000/16904	1000L				


DOSING POTS

	Code	Size (mm)			Code	Size
Dosing Pots Flamco Made 	FLDPOT3.5	565 225 40 220				
	FLDPOT6	670 225 90 220				
	FLDPOT11	935 215 279 200				
	FLDPOT18	1250 215 587 200				
	FLDPOT25	937 270 224 295				
Supplied Fully Assembled Min/Max Temp 5C° / 95C° Max Pressure - 16 Bar Sys Connections - 20mm (¾")						

HVAC

TANKS AND VESSELS

FILL SETS

	Code			Code
System Filling Device  comes with safety valve and pressure gauge 0 - 4 bar. -10°C / 120°C	FLFSET/27097		110 - 1000 Litre Expansion Vessel Fillset  comes with pressure gauge	FL/FLEXCON/27293
			DN15 Fillset  incl Ball/Check Valve + Pressure Reducing Valve + Flex Hose+ball valve	ASFS/015

BUFFER TANKS

	Code	Size		Code	Size	
"PS" Models Heated Hot Water Buffer Tanks 	FLVPS/200	200L	Buffer Tank Insulation For "PS" Models  EPS insulating mantle with a polypropylene outer shell and lid (white, RAL 9010 / white aluminium, RAL 9006).	FLBVINS/18675	200L	
	FLVPS/300	300L		FLBVINS/18678	300L	
	FLVPS/500	500L		FLBVINS/18681	500L	
	FLVPS/600	600L		FLBVINS/18684	600L	
	FLVPS/750	750L		FLBVINS/18690	850L	
	FLVPS/850	850L		FLBVINS/18693	1000L	
	FLVPS/1000	1000L		FLBVINS/18699	1200L	
	FLVPS/1200	1200L		FLBVINS/18702	1500L	
	FLVPS/1500	1500L		FLBVINS/18705	1800L	
	FLVPS/1800	1800L		FLBVINS/18708	2000L	
	FLVPS/2000	2000L		FLBVINS/18711	3000L	
	FLVPS/3000	3000L		FLBVINS/18717	5000L	
	FLVPS/4000	4000L		Buffer Tank Insulation For "PS-K" Models  Vapour-tight insulation for use in chilled water (cooling) installations. Temperature range: -200 °C up to +105°C Thickness: 25 mm (if used as insulation)	FLBVINS/18270	500L
	FLVPS/5000	5000L			FLBVINS/18271	750L
"PS-K" Models Chilled Water Buffer Tanks 	FLVPSK/500	500L	FLBVINS/18272	1000L		
	FLPSK/750	750L	FLBVINS/18273	1500L		
	FLBVPSK/1000	1000L	FLBVINS/18274	2000L		
	FLBVPSK/1500	1500L	FLBVINS/18275	2500L		
	FLBVPSK/2000	2000L	FLBVINS/18276	3000L		
	FLBVPSK/2500	2500L				
	FLBVPSK/3000	3000L				

BRANCHING EQUIPMENT

	Code	Size DN (mm)		Code	Size DN (mm)
Cast Iron Branching Equipment  The T-plus is specially designed to create perfect branches quickly and easily, whilst the system remains in operation. PN25, 120°C	FL/TPLUS/90615	15x15x15	Copper Branching Equipment  The T-plus is specially designed to create perfect branches quickly and easily, whilst the system remains in operation. PN16, 120°C	TPLUSC015	15x15x15
	FL/TPLUS/90620	20x15x20		TPLUSC020	20x15x20
	FL/TPLUS/90626	25x20x25		TPLUSC025	25x20x25
	FL/TPLUS/90632	32x25x32		TPLUSC028	28x20x28
	FL/TPLUS/90640	40x32x40		TPLUSC032	32x20x32
	FL/TPLUS/90650	50x32x50		TPLUSC040	40x20x40
	FL/TPLUS/90665	65x32x65			
	FL/TPLUS/90680	80x32x80			