









PLASTIC VALVES

FOR WATER APPLICATIONS

FIP DOUBLE UNION PVC BALL VALVES					
	Code	Size		Code	Size
VE Ball Valve BSP Ends 	VFIPVEBSP/015	15mm	VE Ball Valve Socketed Ends 	VFIPVE/015	15mm
	VFIPVEBSP/020	20mm		VFIPVE/020	20mm
	VFIPVEBSP/025	25mm		VFIPVE/025	25mm
	VFIPVEBSP/032	32mm		VFIPVE/032	32mm
	VFIPVEBSP/040	40mm		VFIPVE/040	40mm
	VFIPVE/BSP050	50mm		VFIPVE/050	50mm
	VFIPVEBSP/065	65mm		VFIPVE/065	65mm
	VFIPVEBSP/080	80mm		VFIPVE/080	80mm
	VFIPVE/BSP100	100mm		VFIPVE/100	100mm
BSP Valve End 	VAFIPBSP/015	15mm	Socket Valve End 	VAFIPSOCKET/015	15mm
	VAFIPBSP/020	20mm		VAFIPSOCKET/020	20mm
	VAFIPBSP/025	25mm		VAFIPSOCKET/025	25mm
	VAFIPBSP/032	32mm		VAFIPSOCKET/032	32mm
	VAFIPBSP/040	40mm		VAFIPSOCKET/040	40mm
	VAFIPBSP/050	50mm		VAFIPSOCKET/050	50mm
	VAFIPBSP/065	65mm		VAFIPSOCKET/065	65mm
	VAFIPBSP/080	80mm		VAFIPSOCKET/080	80mm
	VAFIPBSP/100	100mm		VAFIPSOCKET/100	100mm



The FIP VE ball valves are ideally suited to conveying water and harmless fluids. The valves are full bore, with double unions and a safe block design offering fully adjustable removable seats. Ball seats are made from PE-PTFE technopolymer with EPDM O-rings. Valves are available with a PVC body, imperial socket and BSP threaded ends.

+GF+ 565 BUTTERFLY VALVES					
	Code	Size		Code	Size
Wafer Style EPDM Seat with Lever Handle 	VGF565/050	50mm	Wafer Style FPM Seat with Lever Handle 	VGF565FPM/050	50mm
	VGF565/065	65mm		VGF565FPM/065	65mm
	VGF565/080	80mm		VGF565FPM/080	80mm
	VGF565/100	100mm		VGF565FPM/100	100mm
	VGF565/125	125mm		VGF565FPM/125	125mm
	VGF565/150	150mm		VGF565FPM/150	150mm
	VGF565/200	200mm		VGF565FPM/200	200mm
Wafer Style EPDM Seat Bare Shaft 	VGF565BS/050	50mm	Wafer Style FPM Seat Bare Shaft 	VGF565FPMBS/050	50mm
	VGF565BS/065	65mm		VGF565FPMBS/065	65mm
	VGF565BS/080	80mm		VGF565FPMBS/080	80mm
	VGF565BS/100	100mm		VGF565FPMBS/100	100mm
	VGF565BS/125	125mm		VGF565FPMBS/125	125mm
	VGF565BS/150	150mm		VGF565FPMBS/150	150mm
	VGF565BS/200	200mm		VGF565FPMBS/200	200mm
	VGF565BS/250	250mm		VGF565FPMBS/250	250mm
VGF565BS/300	300mm	VGF565FPMBS/300	300mm		



The new Butterfly Valve 565 is made out of high-quality plastics that protect it from corrosion and abrasion, and comes in a wafer design with the same installation length as metal solutions (DN50 – DN300). Offering lockable ergonomic lever, standard 5° ratchet setting and optional electric position indicator, along with Data-Matrix-Code and interface for flexible automation (ISO 5211). Fiber reinforced housing and inner disc: PVDF disc and a EPDM or FKM sleeve

PLASTIC VALVES

FOR WATER APPLICATIONS

SPEARS PVC SWING CHECK VALVE					
	Code	Size		Code	Size
Spears PVC Swing Check Valve, White  Socketed	S1520-07	20mm	Spears PVC Spring Check Valve, White  Socketed	S1580-05	15mm
	S1520-10	25mm		S1580-07	20mm
	S1520-12	32mm		S1580-10	25mm
	S1520-15	40mm		S1580-15	40mm
	S1520-20	50mm		S1580-20	50mm
	S1520-30	80mm		S1580-30	80mm
	S1520-40	100mm		S1580-40	100mm
	S1520-60	150mm			

PVC utility swing check valves are ideally suited for a range of applications. Available either with or without a spring, they are an economic solution for ensuring flow in one direction only.

PHILMAC VALVES					
	Code	Size		Code	Size
Philmac Ball Valve 	PHBV/015	15mm	Philmac Spring Check Valve 	PHNV/020	20mm
	PHBV/020	20mm		PHNV/025	25mm
	PHBV/025	25mm		PHNV/032	32mm
	PHBV/032	32mm		PHNV/040	40mm
	PHBV/040	40mm		PHNV/050	50mm
	PHBV/050	50mm			

Philmac valves are manufactured from glass reinforced polypropylene (GRP). Their simple rugged construction makes them ideally suited for use above or below ground in irrigation and water distribution lines.